Date: 10/1/2020



# **Safety Data Sheet**

## **SECTION 1 - MATERIAL IDENTIFICATION**

Trade Name and Synonyms: PliGlue Product Number: 62100

Al<sub>2</sub> O<sub>3</sub> - 9.0 % SiO<sub>2</sub> - 0.0 % **Manufacturers Code I.D.**: 62100

Chemical Name and Synonyms: Al(H<sub>2</sub>PO4)<sub>3</sub> Chemical/Mineral Family: Mono-Aluminum Phosphate

Recommended Use: Refractory/Construction/maintainence/repair material

Supplier: Plibrico Company, LLC - 1935 Techny Road - Unit 16, Northbrook, IL 60062

Phone 312-337-9000, Fax 312-337-9003, www.plibrico.com

Manufacturer: Plibrico Company, LLC - 1935 Techny Road, Unit 16, Northbrook, IL 60062

Phone 312-337-9000, Fax 312-337-9003, www.plibrico.com

Contact Person: Chris Smith, csmith@plibrico.com

EMERGENCY PHONE: 312-337-9000, After 4:30PM weekdays, Weekends, and Holidays: 740-604-1033

## SECTION 2- HAZARDOUS IDENTIFICATION













Signal Word: Danger

Hazard statement: H315: Causes skin irritation,

H320: Causes eye irritation

H335: May cause respiratory irritation H351: Suspected of causing cancer H373: May cause damage to lung through prolonged or repeated inhalation.

## This product contains crystalline silica, a substance that has been listed by:

- 1. IARC: sufficient evidence for the carcinogenicity of crystalline silica to humans. (Group 1)
- 2. Canadian WHMIS: D2A Materials Causing Other Toxic Effects
- 3. ACGIH: A2-Suspected Human Carcinogen.
- 4. NTP: a substance known to be a human carcinogen.

Special Notes: \*\*\* Greater amounts of Quartz and Cristobalite may be formed after firing.

Major portion of the crystalline silica present in the product as manufactured is not fine enough to normally be considered respirable.

#### **Precautionary Statements:**

P260+P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear eye protection/face protection

P285 - Wear respiratory protection

P305+P351+P338 - If in eyes: Rinse cautiously with water.


P302+P352 - If on skin: Wash with plenty of soap and water.

P501- Dispose of material in accordance with local regulation.

# Primary Route of Entry: Inhalation, Ingestion, Skin Contact

#### **Potential Health Effects:**

Mono-aluminum phosphate is a corrosive acid which may cause burns on contact with any part of the body. Similarly, it may cause local damage if taken internally.



# NFPA Rating scale 0-4



Trade Name and Synonyms: PliGlue Date: 10/1/2020 Page 2 of 4

#### **SECTION 3- HAZARDOUS INGREDIENTS**

Ingredients (checked)	C.A.S. No.	Weight %	TLV ACGIH mg/m <sup>3</sup>	OSHA PEL mg/m <sup>3</sup>	EINECS
Quartz***	14808-60-7	7.37	0.025(resp.dust)	$0.05 \text{ mg/m}^3 \text{TWA}$	238-878-
Cristobalite***	14464-46-1		0.025(resp.dust)	$0.05 \text{ mg/m}  ^3\text{TWA}$	238-455-
Amorphous Silica***	69012-64-2		0.025(resp.dust)	15(total), 5(resp.)	273-761-
Fused Silica***	60676-86-0		0.025(resp. dust)	$80 \text{ mg/m}^3/\% \text{SiO} 2$	262-373-
Zirconium Silicate***	14940-68-2		10	15(total), 5(resp.)	239-019-
Aluminum Phosphate	7784-30-7	100	1	2 mg/m <sup>3</sup> TWA(as Al)	232-056-
Alumina	1344-28-1	-	1(resp.dust)	15(total), 5(resp.)	215-691-
Aluminosilicate(Mullite)	1302-93-8	-	2(resp.dust)	15(total), 5(resp.)	215-113-
Aluminosilicate(Kyanite)	1302-76-7	48 58.	2(resp.dust)	15(total), 5(resp.)	215-106-
Bauxite	1318-16-7	-	10	15(total), 5(resp.)	
Silicon Carbide	409-21-2	-	10	15(total), 5(resp.)	206-991
Pyrophyllite	12269-78-2	-	10	15(total), 5(resp.)	
Spinel	1302-67-6	-	10	15(total), 5(resp.)	215-105-
Andalusite	12183-80-1	-	10	15(total), 5(resp.)	235-352
Zirconiumdioxide	1314-23-4	-	10	15(total), 5(resp.)	215-227
Calcium Aluminate Cement	65997-16-2	-	10	15(total), 5(resp.)	266-045
Calcium Silicate Cement	65997-15-1	-	10	15(total), 5(resp.)	266-043
Clay	1332-58-7	17 27.	2(resp.dust)	15(total), 5(resp.)	265-064
Aluminum Sulfate	10043-01-3	-	2(resp.dust)	15(total), 5(resp.)	233-135
Barium Sulfate	772-74-37	-	10	10(total), 5(resp.)	231-784
Bentonite	1302-78-9	-	10	15(total), 5(resp.)	215-108
Perlite	93763-70-3	-	10	15(total), 5(resp.)	310-127
Sodium Silicate	1344-09-8	10 20.	10	15(total), 5(resp.)	215-687-
Titanium Oxide	13463-67-7	1.4	10	15(total), 5(resp.)	215-280
Calcium Fluoride	7789-75-5	1 - 5	2.5 as F	2.5 as F	232-188-
Organic Fiber	9003-07-0	0.05 - 0.5	10(total), 3(resp.)	15(total), 5(resp.)	215.105
olyphosphoric acids, sodium salts	1310-73-2 68915-31-1	< 1 < 5	2 (Ceiling) 3 (resp. dust)	2 TWA 15(total), 5(resp.)	215-185- 272-808

## **SECTION 4- FIRST AID MEASURES**

Rinse affected areas with water. If symptoms persist, seek medical attention.

Eyes: Immediately flush eyes with plenty of water and get medical attention.

Skin: Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion: If swallowed, drink large amounts of water, seek medical attention.

Inhalation: Remove to fresh air. Get medical attention if irritation or discomfort persists. If not breathing, give artificial respiration. Get immediate attention.

#### **SECTION 5- FIRE FIGHTING MEASURES**

**Unusual Fire and Explosive Hazards:** Noncombustible. Though this material is nonflammable, it decomposes on heating, producing toxic fumes of phosphorus oxides (POx). It can react vigorously with metals to liberate hydrogen, a flammable gas. **Fire Fighting Equipment:** Fire fighters should wear full protective gear and self-contained breathing apparatus-SCBA.

# SECTION 6- ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Follow applicable OSHA regulations (29CFR 1910.120)

Cover with dry lime, sodium carbonate or soda ash and carefully scoop up material and place in a closed container. Wash site after material pickup is complete.

**Waste Disposal Method:** Following cleanup, separate solids then precipitate with lime pH 11.0. Contact local sewage authority or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Trade Name and Synonyms: PliGlue Date: 10/1/2020 Page 3 of 4

#### **SECTION 7 - HANDLING AND STORAGE**

Precautions to be taken in handling and storage: Keep closed in well ventilated area and do not allow to freeze.

## SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Ventilation: Local and Mechanical: follow OSHA STD 29 CFR 1910.94.

Respiratory Protection: Use in a well ventilated area with local exhaust to maintain airborne concentration below OSHA Pels. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29.CFR1910.134) and, if necessary, wear MSHA/NIOSH approved respirator.

Protection Gloves: Acid Resistant Protective gloves recommended.

Eye Protection: Splash proof chemical safety goggles.

Other Protective Equipment: As required to meet applicable OSHA standards.







## **SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES**

Appearance, Color & Odor: Milky liquid, phosphoric acid odor. pH - 1, pH of 1 % solution, 2 - 2.5

Solubility in Water: Complete

Boiling Point (°): 1atm, > 2120F, 1000C Vapor Pressure at 20°C: 0.029mm Hg

Specific Gravity: 1.58 % Volatile by Volume: 53% (water)

Crystallization Point: -10°F

# **SECTION 10- STABILITY AND REACTIVITY DATA**

Stability: Stable Incompatibility: Avoid oxidizing agents, acids, acid chlorides, acid anhydrides

Hazardous Polymerization: May not occur

Hazardous Decomposition: Decomposes on heating, producing toxic fumes of phosphorus oxides (POx)

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

Target Organs / Effects of overexposure: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

Inhalation: Acute (Immediate): Exposure to fumes/nuisance dust may cause temporary irritation or discomfort to skin, eyes, nose, throat or lungs and may aggravate bronchial disorders. Chronic (Delayed): Long term inhalation may cause lung injury and other respiratory disorders.

Skin: GHS Properties: Skin corrosion/Irritation: OSHA HCS 2012, EU/CLP • Skin Corrosion 1B Acute: Causes severe skin burns. Chronic: Repeated or prolonged exposure to corrosive materials will cause dermatitis.

**Eye:** Acute: Corrosive. Can cause permanent damage to the cornea, blindness. Chronic: Repeated or prolonged exposure to corrosive materials or fumes may cause conjunctivitis.

**Ingestion:** Acute: Causes corrosion, burns to mouth and esophagus, abdominal pain, chest pain, nausea, vomiting, diarrhea, seizures. Aspiration of the swallowed or vomited product can cause severe pulmonary complications. Chronic: Repeated or prolonged exposure to corrosive materials or fumes may cause gastrointestinal disturbances.

GHS Classification for the GHS properties including Acute toxicity, Aspiration Hazard, Carcinogenicity, Germ Cell Muta-genicity, Skin sensitization, STOT-RE, STOT-SE, Toxicity for Reproduction, Respiratory sensitization, Serious eye dam-age/Irritation: OSHA HCS 2012, EU/CLP: Data lacking or Classification criteria not met.

#### SECTION 12 - ECOLOGICAL INFORMATION

No ecological concerns have been identified.

- 12.1 Toxicity
- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in Soil
- 12.5 Results of PBT and vPvB assessment
- 12.6 Other adverse effects: Ecological Fate: No data found
- 12.7 Other Information: No specific biodegradation test data located.

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Following cleanup, separate solids then precipitate with lime pH 11.0.

Contact local sewage authority or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Date: 10/1/2020 Page 4 of 4 Trade Name and Synonyms: PliGlue

#### **SECTION 14 - TRANSPORT INFORMATION**

Canadian Transportation of Dangerous Goods Regulation: Hazard Class & PIN: Corrosive Liquid, N.O.S., 8, UN1760

DOT Proper Shipping Name (29 CFR 172.101): Buffered Mono-Aluminum Phosphate Solution (phosphoric acid 44%)

DOT Hazard Class (29 CFR 172.101), ADR/RID/AND, IMDG, ICAO: 8 Corrosive

UN/NA Code (49 CFR 172.101), ADR/RID/AND, IMDG, ICAO: UN1805

DOT Labels Required (49 CFR 172.101), ADR/RID/AND, IMDG, ICAO: 8 Corrosive

DOT Placards Required (49 CFR 172.504), ADR/RID/AND, IMDG, ICAO: 8 Corrosive

Package group -ADR/RID/AND, IMDG, ICAO: Group III

## **SECTION 15 - REGULATORY INFORMATION**

CANADIAN WHMIS: Classification: E; Ingredient Disclosure List: 1% for Phosphoric acid **CANADIAN EPA**: Components of this product are listed on the Domestic Substance List (DSL).

U.S. FEDERAL REGULATIONS: for Phosphoric acid 7664-38-2

U.S. OSHA Process Safety Management: Highly Hazardous Chemicals: Not Listed

U.S. OSHA Specifically Regulated Chemicals: Not Listed

U.S. CAA (Clean Air Act): 1990 Hazardous Air Pollutants: Not Listed

U.S. CAA (Clean Air Act): Class II Ozone Depletors: Not Listed

U.S. CERCLA/SARA - Hazardous Substances and their Reportable Quantities:

5000 lb final RQ; 2270 kg final RQ as listed in Appendix A to 49 CFR 172.101. U.S. CERCLA/SARA: Radionuclides and Their Reportable Quantities: Not Listed

U.S. CERCLA/SARA: Section 302 Extremely Hazardous Substances EPCRA RQs: Not Listed

U.S. CERCLA/SARA: Section 302 Extremely Hazardous Substances TPQs: Not Listed

U.S. CERCLA/SARA: Section 313 - Emission Reporting: Not Listed

U.S. CERCLA/SARA: Section 313 - PBT Chemical Listing: Not Listed

**TSCA**: Components of this product are listed on the TSCA Inventory.

## **SECTION 16 - OTHER INFORMATION**

Only Trained personel should use this material.

Abbreviations:

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation and Liability Act

DOT: Department of Transportation EPA: Environmental Protection Agency

IARC: International Agency for Research on Cancer

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration SARA: Superfund Amendment and Reauthorization Act

WHMIS: Workplace Hazardous Materials Information System (Canada)

#### DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Safety Data Sheet. Occupational exposure limits are under constant review and may be changed at any time. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of this product. This summary of the relevant data reflects professional judgment. Employers should note that information perceived to be less relevant has not been included in this SDS. Therefore, given the summary nature of this document, Plibrico Company, LLC, does not extend any warranty (expressed or implied), assume any responsibility or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user. No warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use. In addition, Plibrico Company, LLC, shall not be liable for injury arising by either misuse of materials, or failure to follow safety procedures as outlined in the safety data sheet.